


MVSY-100 系列

電磁閥



規格：


型號	4E1	4E2	4E2C.P.R
配管口徑代號	M5		
配管口徑尺寸	M5×0.8		
方口數	5口		
位置數	2位置		3位置
使用流體	空氣		
使用壓力範圍	0.2~0.7 MPa		
耐壓力	1 MPa		
有效斷面積	直配管型	4.5 mm ²	4.5 mm ²
	連座型	4.5 mm ²	4.5 / 5 / 4.5 mm ²
應答時間	12 ms		15 ms
周圍溫度	+5~+50℃		
最大工作頻率	5 Hz		
定格電壓	AC110V, AC220V(50/60)Hz, DC6/12/24V		
電力消耗	AC=1.6/2.5VA, DC6=1.2W, DC12/24=0.55W		
電壓容許範圍	±10%		
絕緣等級	B 級		
重量	30g	43g	55g

注意事項：

- 電磁閥不可連續通電超過2小時以上。
- 以一天為單位，電磁閥總通電時間不可超過未通電時間。


閥 / 訂購代號：

MVSY - 100M - 4E2C - AC110 - LJ1




連座 / 訂購代號：

MVSY - 100M - 5M3 - G



導線 / 訂購代號：※ 與 MVDY 共用導線

MVDY - 100 - WA2J2





MVSY-100 外觀尺寸

電磁閥





MVSY-100-4E1

() : LJ 出線型式尺寸



MVSY-100-4E2

() : LJ 出線型式尺寸







MVSY-100-4E2C.PR


MVSY-100-4E2C

MVSY-100-4E2P

MVSY-100-4E2R



流量特性圖：



() : LJ 出線型式尺寸


MVSY-100 連座

電磁閥



MVSY-100-5B*

5方口直配管型用




連座數	P	L
2	30.5	48.5
3	41	59
4	51.5	69.5
5	62	80
6	72.5	90.5
7	83	101
8	93.5	111.5
9	104	122
10	114.5	132.5

() : LJ 出線型式尺寸

MVSY-100M-5M*

5方口連座型用



連座數(N)	P	L
2	39.5	47.5
3	52	60
4	64.5	72.5
5	77	85
6	89.5	97.5
7	102	110
8	114.5	122.5
9	127	135
10	139.5	147.5

() : LJ 出線型式尺寸

MVSY-100 安裝配件

電磁閥





支架 / 訂購代號：

MVSY-100-1A

安裝配件
1A：支架
2A：腳架

MVSY-100-1A

支架



MVSY-100-2A

腳架

